S Permatex

SAFETY DATA SHEET

Revision Date 04-Mar-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name

26C HIGH TEMP RED RTV SILICONE GASKET MAKER 110Z

Other means of identification

Product Code

81409

Synonyms

•

None

Recommended use of the chemical and restrictions on use

Recommended Use

Sealant

Uses advised against

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Distributor

ITW Permatex

ITW Permatex Canada

10 Columbus Blvd.

35 Brownridge Road, Unit 1

Hartford, CT 06106 USA

Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number

1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number

Chem-Tel: 800-255-3924 International Emergency:

00+1+ 813-248-0585

Contract Number: MIS0003453

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A

Label elements

Eme	rgency	y Ov	erv	iew

Warning

Causes skin irritation

Causes serious eye irritation



Appearance Red

Physical state Paste

Odor Acetic acid

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Protect from moisture

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen. This note applies only to certain complex oil derived substances in Annex I

Unknown acute toxicity

12.3% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No	Weight-%	Trade Secret
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED	70131-67-8	40 - 70	•
AMORPHOUS SILICA	7631-86-9	7 - 13	*
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE	64742-46-7	3 - 7	•
IRON OXIDE	1309-37-1	1 - 5	*
TITANIUM DIOXIDE	13463-67-7	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

81409 - 26C HIGH TEMP RED RTV SILICONE GASKET MAKER 110Z

Revision Date 04-Mar-2015

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person.

Self-protection of the first aider Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

See section 2 for more information. **Symptoms**

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact

None None.

Sensitivity to Static Discharge

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Personal precautions

Use personal protective equipment as required.

Environmental precautions

Do not flush into surface water or sanitary sewer system. See Section 12 for additional **Environmental precautions**

ecological information.

Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Methods for containment

Methods for cleaning up Ensure adequate ventilation. Flood with water to complete polymerization and scrape off

floor. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse.

•

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture.

Incompatible materials

Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
AMORPHOUS SILICA	-	(vacated) TWA: 6 mg/m³ <1%	IDLH: 3000 mg/m ³
7631-86-9		Crystalline silica	TWA: 6 mg/m ³
	-	TWA: 20 mppcf	•
		: (80)/(% SiO2) mg/m³ TWA	
IRON OXIDE	TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m ³ fume	IDLH: 2500 mg/m³ Fe dust and
1309-37-1		TWA: 15 mg/m³ total dust	fume
		TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m³ Fe dust and fume
'		(vacated) TWA: 10 mg/m³ fume	'
1		and total dust Iron oxide	
1		(vacated) TWA: 5 mg/m³ respirable	
		fraction regulated under Rouge	
TITANIUM DIOXIDE	TWA: 10 mg/m ³	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m ³
13463-67-7		(vacated) TWA: 10 mg/m³ total dust	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Remarks • Method

Polymerization

Tag Closed Cup

Butyl acetate = 1

Air = 1

Polymerization

Information on basic physical and chemical properties

Physical state **Appearance**

Paste Red

Odor

Acetic acid

Odor threshold

No information available

Property pН

Values

Does not apply No information available

Melting point / freezing point Boiling point / boiling range Flash point

Not Applicable > 93 °C / > 199 °F

<1

Evaporation rate Flammability (solid, gas)

No information available

Flammability Limit in Air Upper flammability limit:

No information available No information available

Lower flammability limit: Vapor pressure Vapor density

10 mm Hg

Relative density

>1

1.05

Not applicable

Water solubility Solubility in other solvents No information available Partition coefficient

Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity **Explosive properties Oxidizing properties**

No information available No information available

Other Information

Softening point Molecular weight No information available No information available <3%

VOC Content (%)

Density Bulk density

No information available

No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat. Exposure to air or moisture over prolonged periods.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides, Nitrogen oxides (NOx), Formaldehyde, May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

May cause irritation of respiratory tract.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis.

Ingestion

Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	.	> 16 mL/kg(Rabbit)	> 8750 mg/m³(Rat)7 h
AMORPHOUS SILICA 7631-86-9	> 5000 mg/kg(Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat)1 h
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	= 7400 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	= 4.6 mg/L (Rat)4h
IRON OXIDE 1309-37-1	> 10000 mg/kg (Rat)	-	-
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	· •	-

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Germ cell mutagenicity

No information available.

 Carcinogenicity
 The table below indicates whether each agency has listed any ingredient as a carcinogen.

 Chemical Name
 ACGIH
 IARC
 NTP
 OSHA

Chemical Name	ACGIN	IANC	IN IT.	USHA
AMORPHOUS SILICA	-	Group 3	-	-
7631-86-9				
IRON OXIDE	-	Group 3	-	-
1309-37-1				
TITANIUM DIOXIDE	-	Group 2B	-	, X
13463-67-7			1	

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects

Eyes, Lungs, Respiratory system, Skin, Teeth.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)

17289 mg/kg

ATEmix (dermal)

6094 mg/kg

ATEmix (inhalation-dust/mist)

4.8 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

82.1% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea

AMORPHOUS SILICA	440: 72 h Pseudokirchneriella	5000: 96 h Brachydanio rerio mg/L	7600: 48 h Ceriodaphnia dubia
7631-86-9	subcapitata mg/L EC50	LC50 static	mg/L EC50
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	-	35: 96 h Pimephales promelas mg/L LC50 flow-through 10000: 96 h Pimephales promelas mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT

Proper shipping name:

Not regulated

Proper shipping name:

Not regulated

IMDG

Proper shipping name:

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA

Complies

DSL/NDSL

Complies

EINECS/ELINCS

Does not comply Does not comply

ENCS IECSC

Complies

KECL

Complies

PICCS

AICS

Complies Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
TITANIUM DIOXIDE - 13463-67-7	Carcinogen
HO OLI DI LILI IV. D. LIII	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
AMORPHOUS SILICA 7631-86-9	Χ	Х	X
IRON OXIDE 1309-37-1	Х	X	Х
TITANIUM DIOXIDE 13463-67-7	X	X	Х
ACETIC ACID 64-19-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA	Health hazards 1	Flammability 1	Instability 0	-
<u>HMIS</u>	Health hazards 1	Flammability 1	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

04-Mar-2015

81409 - 26C HIGH TEMP RED RTV SILICONE GASKET MAKER 110Z

Revision Date 04-Mar-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet